


ACS Soffit Restraint



Technical Data

The ACS Soffit Restraint is an adjustable restraint designed to provide lateral restraint to the head of an internal wall or the internal leaf of a cavity wall.

The Soffit Restraint is suitable for restraining blocks ranging from 100 - 140mm thick as standard, restraints to suit alternative block sizes can be manufactured on request. A maximum offset of 25mm from the head of the wall to be restrained to the underside of the structure must be achieved. A standard Soffit Restraint is designed to be used with an M8 fixing, fixed through the 10mm diameter hole / slot in the restraint, this fixing would not be supplied as standard but is available on request.

The restraint is available in austenitic stainless steel grades 304 (BS EN 1.4301) and 316 (BS EN 1.4401) and provides a declared load capacity of 1kN.

For further information or technical assistance please contact the ACS Technical Department on 0844 850 0860 or email technical@acsstainless.co.uk

LEEDS
Cross Green Approach
Cross Green Industrial Park
Leeds LS9 0SG
Tel: +44 (0)113 391 8200
Fax: +44 (0)113 391 8209

LONDON
Crown House
Home Gardens
Dartford
Tel: +44 (0)1322 424 510
Fax: +44 (0)1322 424 504

GLASGOW
Festival House
150 Brand Street
Glasgow G51 1DH
Tel: +44 (0)141 314 0048
Fax: +44 (0)141 314 0026

